



CULVERT SIZING (LOTS 1-24 & 56-75)

NOTES:

1. DRIVEWAYS MUST BE CENTERED ON LOT WITH AT LEAST 150' SPACING BETWEEN DRIVEWAYS IF POSSIBLE.
2. MUST INCLUDE A 15" MINIMUM CMP CULVERT WITH 4:1 SAFETY END TREATMENT.
3. ALL-WEATHER SURFACE

LOT	TYPE	SIZE
1	N/A	N/A
2	N/A	N/A
3	N/A	N/A
4	N/A	N/A
5	N/A	N/A
6	CMP	18"
7	CMP	18"
8	N/A	N/A
9	N/A	N/A
10	N/A	N/A
11	N/A	N/A
12	CMP	18"
13	CMP	18"
14	CMP	18"
15	CMP	18"
16	CMP	18"
17	N/A	N/A
18	N/A	N/A
19	CMP	18"
20	CMP	18"
21	CMP	18"

LOT	TYPE	SIZE
22	CMP	18"
23	CMP	18"
24	CMP	18"
56	CMP	30"
57	CMP	18"
58	CMP	24"
59	CMP	30"
60	CMP	30"
61	N/A	N/A
62	CMP	18"
63	CMP	18"
64	N/A	N/A
65	N/A	N/A
66	CMP	18"
67	CMP	18"
68	CMP	18"
69	CMP	24"
70	N/A	N/A
71	CMP	18"
72	CMP	24"
73	CMP	30"
74	CMP	2-24"
75	CMP	2-30"